

Quality Control Certificate

Product: Universal Column

Product No.: 19511 **Lot No.: 720976**

Storage Recommendations: Store the column at room temperature below 25°C

Description: The Universal Column is part of a 3- or 4-column setup used for the sample

preparation of environmental-, food- $\!\!\!/$ feed- and similar matrices with DEXTech systems from LCTech for the analysis of polychlorinated dibenzo-p-dioxins (PCDD),

polychlorinated dibenzofurans (PCDF) and polychlorinated biphenyl (PCB)

congeners.

Quality Control Release Inspection and Test Specification

Test Procedure: A solvent blank, spiked with quantification standard has been cleaned on a

DEXTech Plus system, spiked with recovery standard, evaporated with the D-EVA and has been quantified with a HRGC/HRMS DFS from Thermo Fisher Scientific at a

resolution of R > 10000.

Results Blank Value: PCDD/F-TEQ: 0,17 pg/column

(crit: < 0,70 pg/column)

dl-PCB-TEQ: 0,0307 pg/column

(crit: < 0,05 pg/column)

Sum Total PCB: 4,8 pg/column

(crit: < 300 pg/column)

Results Recoveries: PCDD/F 89 to 106 % (crit: 70 to 120 %)

PCB 83 to 107 % (crit: 70 to 120 %)

This is to certify that the Universal Column, Lot 720976, passed the required test specifications and is released for sale.

date: 25.10.2024 sign.:

The company LCTech GmbH is certified according to ISO 9001





QC-Certificate - 19511 - 720976

Hazards: NOT FOR HUMAN OR DRUG USE!

The Universal Column is designed and prepared for usage with the Alumina/Florisil Column and Carbon Column from LCTech and for laboratory use only. This product should only be used by qualified personnel familiar with its potential hazards and trained in the handling of hazardous chemicals. Due care should be exercised to prevent unnecessary human contact or ingestion, all procedures should be carried out with suitable gloves, eye protection, and clothing should be worn at all times. Waste should be disposed according to national and regional regulations.

Quality Control: All ingredients are traceable to certified lots of our supplier. In addition, any

ingredient with a new lot will be checked on contamination and efficiency before releasing for production. Monitoring the ongoing production, several columns are chosen at random day for analysis to check on contamination

and efficiency.

Quality Management: This product was produced using a Quality Management System registered to the

ISO 9001:2015 (DEKRA)

Documentation / table 1 & 2: blankvalues of PCDD/F and PCB
Data Attached: table 3 & 4: 13C-Recoveries of PCDD/F and PCB

Analytics This is to certify that the Universal Column, Lot , passed the required test

specifications and is released for sale.

Remarks Our suppliers maintain the highest standard of quality, however due to the high

temperature necessary for several steps in the production, some small charred particles may be visible within a batch of silica or filters without any effect on the

clean-up.





QC-Certificate - 19511 - 720976

Results:

Lockmass check: No significant disturbances, or indicators for contaminations are detected.

Blanks: n= 9

Table 1: PCDD/F blank

	_	[pg/column]
	2,3,7,8-TCDF	0,09
	1,2,3,7,8-PeCDF	<0,045
	2,3,4,7,8-PeCDF	<dl< td=""></dl<>
٦	1,2,3,4,7,8-HxCDF	0,039
I I	1,2,3,6,7,8-HxCDF	0,029
<u> </u>	2,3,4,6,7,8-HxCDF	<0,045
/gd]	1,2,3,7,8,9-HxCDF	0,06
≗	1,2,3,4,6,7,8-HpCDF	0,23
I I	1,2,3,4,7,8,9-HpCDF	0,057
amo	1,2,3,4,6,7,8,9-OCDF	0,06
a	2,3,7,8-TCDD	<0,036
o e	1,2,3,7,8-PeCDD	0,06
sample	1,2,3,4,7,8-HxCDD	0,086
SS	1,2,3,6,7,8-HxCDD	0,23
	1,2,3,7,8,9-HxCDD	0,159
	1,2,3,4,6,7,8-HpCDD	0,18
	1,2,3,4,6,7,8,9-OCDD	1,93

PCDD/F TEQ (2005)	[pg/column]	
lower bound		0,16
upper bound		0,17

Table 2: PCB blank

		[pg/column]
	PCB-#28	2,92
	PCB-#52	0,65
	PCB-#101	0,37
	PCB-#153	0,58
<u>[e</u>	PCB-#138	0,29
п	PCB-#180	<dl< td=""></dl<>
/sa	PCB-#81	0,15
sample amount [pg/sample]	PCB-#77	0,275
Ħ	PCB-#126	0,2554
no	PCB-#169	0,17
au	PCB-#123	0,01
<u>e</u>	PCB-#118	0,12
ш	PCB-#114	0,023
sal	PCB-#105	0,12
	PCB-#167	<dl< td=""></dl<>
	PCB-#156	<dl< td=""></dl<>
	PCB-#157	<dl< td=""></dl<>
	PCB-#189	0,344

PCB-TEQ	[pg/column]
lower bound	0,0307
upper bound	0,0307
Sum DIN	4,8





QC-Certificate - 19511 - 720976

Table 3: PCDD/F recoveries

		[%]	RSD [%]
	2,3,7,8-TCDF	93	5
	1,2,3,7,8-PeCDF	93	4
	2,3,4,7,8-PeCDF	92	7
[%	1,2,3,4,7,8-HxCDF	93	5
ွှ	1,2,3,6,7,8-HxCDF	105	4
rie.	2,3,4,6,7,8-HxCDF	103	6
Recoveries [%]	1,2,3,7,8,9-HxCDF	99	5
	1,2,3,4,6,7,8-HpCDF	106	5
	1,2,3,4,7,8,9-HpCDF	97	14
30	1,2,3,4,6,7,8,9-OCDF	104	7
-	2,3,7,8-TCDD	89	2
5	1,2,3,7,8-PeCDD	94	6
PCDD/F 13C	1,2,3,4,7,8-HxCDD	101	5
٩	1,2,3,6,7,8-HxCDD	91	5
	1,2,3,7,8,9-HxCDD	104	5
	1,2,3,4,6,7,8-HpCDD	101	6
	1,2,3,4,6,7,8,9-OCDD	95	8

Table 4: PCB recoveries

		[%]	RSD [%]
	PCB-#28	99	8
	PCB-#52	107	7
	PCB-#101	98	5
	PCB-#153	99	3
5	PCB-#138	104	5
<u>%</u>	PCB-#180	98	7
<u>ië</u>	PCB-#81	98	5
PCB 13C Recoveries [%]	PCB-#77	100	4
	PCB-#126	104	6
	PCB-#169	106	9
3	PCB-#123	88	8
PCB 13	PCB-#118	90	12
	PCB-#114	91	5
	PCB-#105	83	11
	PCB-#167	86	12
	PCB-#156	91	7
	PCB-#157	91	11
	PCB-#189	94	11

